


SG75CX-P2

Multi-MPPT String Inverter for 1000 Vdc System



HIGH YIELD

- 8 MPPTs with max. efficiency 98.5%
- DC 15A current input, compatible with over 500W+ PV module
- Dynamic shading optimization mode



LOWER INVESTMENT

- Compatible max. 240mm² Al AC cables
- Drawer-style cable sealing plate support AC cable pre-assembly



PROVEN SAFETY


- IP66 protection and C5 Anti-corrosion
- DC Type I+II SPD, AC Type II SPD
- Support AFCI 2.0 function




SMART O&M

- Key component diagnosis and protection
- Smart IV Curve Diagnosis
- Grid fault record function, easy for remote O&M

CIRCUIT DIAGRAM



EFFICIENCY CURVE



Type designation	SG75CX-P2
Input (DC)	
Recommended max. PV input power	105 kWp
Max. PV input voltage *	1100 V
Min. PV input voltage / Startup input voltage	180 V / 200 V
Rated PV input voltage	600 V
MPPT operating voltage range **	180 V - 1000 V
No. of independent MPP inputs	8
No. of PV strings per MPPT	2
Max. PV input current	240 A (30 A * 8)
Max. DC short-circuit current	320 A (40 A * 8)
Max. current for DC connector	30 A
Output (AC)	
Rated AC output power	75 kW (415 V @ 50°C) ***
Max. AC output apparent power	75 kW (415 V @ 50°C) ***
Max. AC output current	108.7 A
Rated AC output current (at 230V)	108.7 A
Rated AC voltage	3 / N / PE, 230 V / 400 V ; 3 / N / PE, 240 V / 415 V
AC voltage range	320 V - 480 V
Rated grid frequency	50 Hz / 60 Hz
Grid frequency range	45 Hz – 55 Hz / 55 Hz – 65 Hz
Harmonic (THD)	< 3 % (at rated power)
Power factor at rated power / Adjustable power factor	> 0.99 / 0.8 leading – 0.8 lagging
Feed-in phases / AC connection	3 / 3 - N - PE
Efficiency	
Max. efficiency / European efficiency	98.5 % / 98.3 %
Protection & function	
Grid monitoring	Yes
DC reverse polarity protection	Yes
AC short-circuit protection	Yes
Leakage current protection	Yes
Surge protection	DC Type I+II / AC Type II
Ground fault monitoring	Yes
DC switch	Yes
PV string monitoring	Yes
Q at night function	Yes
Arc fault circuit interrupter (AFCI)	Yes
PID recovery function	Yes
General data	
Dimensions (W * H * D)	1020 mm * 795 mm * 360 mm
Mounting method	Wall-mounting bracket
Weight	82 kg
Topology	Transformerless
Degree of protection	IP66
Corrosion	C5
Operating ambient temperature range	-30 °C - 60 °C
Allowable relative humidity range (non-condensing)	0 % - 100 %
Cooling method	Smart forced air cooling
Max. operating altitude	4000 m
Display	LED, Bluetooth + APP
Communication	RS485 / WLAN / Optional: Ethernet
DC connection type	EVO2 (Max. 6 mm²)
AC connection type	OT / DT terminal (Max. 240 mm²)
Grid compliance	IEC 62109-1, EN/IEC 61000-6-1/2/3/4, IEC 61727, IEC 62116, EN 50549-1/2, UTE C15-712-1, VDE V 0126-1-1, VDE-AR-N 4105:2018, VFR 2019, NC RfG, G99, UNE 217002, NTS, CEI 0-21 2019, CEI0-16 2019, NRS-097-2-1, IEC 63027
Grid support	Q at night function, LVRT, HVRT, active & reactive power control and power ramp rate control

* Input voltage exceeding the MPPT operating voltage range triggers inverter protection.

** Please refer to the user manual for the full load MPPT voltage range.

*** PV input voltage need over 630VDC.